

Overview



SITRANS FUG1010 clamp-on non-intrusive ultrasonic flow transmitter is ideal for natural and process gas applications, including checkmetering, allocation, production, storage and gas fired power station applications.

SITRANS FUG1010 is available in single, dual and optional four path configurations, with your choice of IP65 (NEMA 4X) wall mount, IP65 (NEMA 7) compact explosionproof, and IP66 (NEMA 7) wall mount explosionproof enclosures.

Benefits

- Easy installation; no need to cut pipe or stop flow
- Minimal maintenance; external sensors do not require periodic cleaning
- No moving parts to foul or wear as found in turbine and PD meters
- Eliminates the pressure drop or energy loss in orifice metering
- Wide turn-down ratio
- Choice of single, dual or optional four path versions
 - Single path version reduces initial investment
 - Multiple path versions provide higher accuracy, especially with limited straight run and poor flow profile conditions
 - In diametric reflect mode configuration, the meter is less sensitive to crossflow and swirl
- Wide-Beam technology provides improved accuracy over a wide range of flow velocity and operating pressure
- ZeroMatic Path automatically sets zero without stopping flow and reduces zero drift, even at low flow
- Tolerant of most wet gas conditions
- Immune to most pressure reducing valve noise
- Optional rugged stainless steel sensor enclosure permits permanent and direct burial installations
- Easy to use "Si-Ware" diagnostic software

Application

SITRANS FUG1010 is ideal for most natural and process gas industry applications, including:

- Checkmetering
- Allocation
- Flow survey verification
- Lost and unaccounted for (LAUF) gas analysis
- Production
- Storage

Design

SITRANS FUG1010 is available in three enclosures:

- IP65 (NEMA 4X) wall mount enclosure constructed of fiber-glass reinforced polyester with stainless steel hardware and polyester keypad
 - Single path
 - Dual path
 - Four path (optional)
- IP65 (NEMA 7) compact explosionproof enclosure constructed of cast aluminum with glass window, stainless steel hardware
 - Single path
 - Dual path
- IP66 (NEMA 7) wall mount explosionproof enclosure constructed of cast aluminum stainless steel hardware, with glass window
 - Single path
 - Dual path
 - Four path (optional)

Function

- IP65 (NEMA 4X) and IP66 (NEMA 7) flow display transmitters have integral 33 button keypads and large (128 x 240 pixel) graphic displays visible up to 12 m (40 ft) away
- IP65 (NEMA 7) compact flow transmitter has a 2 x 16 alphanumeric LCD display
- Current, voltage, frequency and RS 232 outputs (see specification section for details)
- Analog inputs for pressure and temperature
- ZeroMatic Path automatically compensates for zero flow drift
- Bidirectional flow operation
- 1 Mbyte data logger with both site and data logger storage
- English, Spanish, German, Italian and French language options
- Internal AGA-8 table for fixed gas composition is available for standard volume computation.
- Complete application and operation diagnostics, to assure calibration and operational integrity
- Upward compatibility and compliance with AGA-10 speed of sound measurement practice

Flow Measurement

SITRANS F US Clamp-on

SITRANS FUG1010 (Gas)

Technical specifications

Input		Accuracy	
Flow range	± 30 m/s (± 100 ft/s), bidirectional	Typical accuracy	1 % ... 2 % of actual volume reading (higher accuracy is pipe condition and flow profile dependent)
Flow sensitivity	0.0003 m/s (0.001 ft/s), flow rate independent	Calibratable Accuracy	± 0.2 ... 0.5 % of flow
Minimum pressure	7 ... 10 bar (100 ... 145 psi), typical (gas composition and application dependent; plastic pipes support operation at atmospheric pressure)	Repeatability	0.05 % ... 0.1 %, of actual volume reading, for 1.5 ... 30 m/s (5 ... 100 ft/s) velocities (pipe condition dependent)
Pipe size	25 mm ... 1.52 m (1" ... 48") (for other sizes, consult factory)	Zero drift	0.0003 m/s (0.001 ft/s), with ZeroMatic Path active
Analog inputs	Current: 20 mA, programmable (IP65 (NEMA 7) enclosure has 20 mA, programmable)	Data refresh rate	5 Hz
Output		Rated operation conditions	
Standard outputs	<ul style="list-style-type: none"> Current: 20 mA, a programmable, standard Additional 2 x optional, except IP65 (NEMA 7) Voltage: 10 V DC, menu programmable (None for IP65 (NEMA 7) enclosure) Open collector digital pulses (quadrature) (None for IP65 (NEMA 7) enclosure) Pulse rate: 5 kHz (None for IP65 (NEMA 7) enclosure) Optically isolated digital pulse & source, IP65 (NEMA 7) enclosure only VT100 RS 232 	Degree of protection	<ul style="list-style-type: none"> Wall mount IP65 (NEMA 4X) Compact explosionproof IP65 (NEMA 7) Wall mount explosionproof IP66 (NEMA 7)
Extended outputs	<ul style="list-style-type: none"> HART, BACnet MSTP/BACnet IP, Modbus RTU & TCP/IP, Ethernet IP, Johnson N2 	Gas temperature	-40 ... +60 °C (-40 ... +140 °F) (for higher temperatures consult factory)
Status/Alarm I/O	<ul style="list-style-type: none"> Programmable form C relays (not for IP65 (NEMA 7) enclosure) Programmable N.O. Mer. Wet. Relays optional (not for IP65 (NEMA 7) enclosure) Optically coupled output logic gates (for IP65 (NEMA 7) enclosure, only) 1 Totalizer clear switch input (not for IP65 (NEMA 7)) 1 Totalizer hold switch input (not for IP65 (NEMA 7) enclosure) Opto iso. totalizer clear switch input (for IP65 (NEMA 7) enclosure, only) Opto iso. totalizer hold switch input (for IP 65 (NEMA 7) enclosure, only) 	Ambient temperature	-18 ... +60 °C (0 ... 140 °F)
		Design	
		Dimensions	see SITRANS F US Clamp-on "System info and selection guide"
		Weight	see diagrams
		Power supply	
		<ul style="list-style-type: none"> For IP65 (NEMA 4X) and IP66 (NEMA 7) 	<ul style="list-style-type: none"> 90 ... 240 V AC, 50 ... 60 Hz (30 VA) or 9 ... 36 V DC (12 W)
		<ul style="list-style-type: none"> For IP65 (NEMA 7): 	<ul style="list-style-type: none"> 90 ... 240 V AC, 50 ... 60 Hz (15 VA) or 9 ... 36 V DC (10 W)
		Indication and operation	
		Data logger memory	1 Mbyte, programmable for 17 data functions
		Display	<ul style="list-style-type: none"> IP65 (NEMA 4X) and IP66 (NEMA 7) enclosures 128 x 240 pixel LCD with back-light IP65 (NEMA 7) enclosure 2 x 16 alphanumeric LCD display
		Keypad	<ul style="list-style-type: none"> IP65 (NEMA 4X) and IP66 (NEMA 7) Enclosures 33 keypad buttons with tactile feedback IP65 (NEMA 7) Enclosure 5 magnetic hall effect switches
		Language options	English, Spanish, German, Italian, French

Certificates and approvalsIP65 (NEMA 4X) wall mount flow display transmitter ratings

FM and CSA

- Transmitter
N-I Class I, Div 2
S Class II, Div 2

- Sensor
I.S. Class I, II, Div 1

CE

EMC Directive 2004/108/EC
ATEX Directive 94/9/EC

C-TICK

ATEX

- Transmitter:
Ex II (1) G [Ex ia] IIC
Ex II 3 (1) G Ex nC [ia] IIC T5

- Sensors:
Ex II 1 G Ex ia IIC T5

IP65 (NEMA 7) compact explosion-proof enclosure ratings

FM and CSA

- Transmitter
XP Class I, Div 1
D-I Class II, Div 1
N-I Class I, Div 2
S Class II, Div 2

- Sensor
I.S. Class I, II, Div 1

CE

EMC Directive 2004/108/EC
ATEX Directive 94/9/EC

C-TICK

ATEX

- Transmitter:
Ex II 2 (1) G Ex d [ia] IIB + H2 T5

- Sensors:
Ex II 1 G Ex ia IIC T5

IP66 (NEMA 7) wall mount explosionproof enclosure ratings

FM and CSA

- Transmitter
XP Class I, Div 1
D-I Class II, Div 1
N-I Class I, Div 2
S Class II, Div 2

- Sensor
I.S. Class I, II, Div 1

CE

EMC Directive 2004/108/EC
ATEX Directive 94/9/EC

C-TICK

ATEX

- Transmitter:
Ex II (1) G [Ex ia] IIC
Ex II 3 (1) G Ex nC [ia] IIC T5
Ex II 2 (1) G Ex d [ia IIC] IIB+H2 T5

- Sensors:
Ex II 1 G Ex ia IIC T5

Selection and Ordering data	Article No.	Ord. code	Selection and Ordering data	Article No.	Ord. code
SITRANS FUG1010 (Gas)			SITRANS FUG1010 (Gas)		
• IP65 (NEMA 4X) wall mount	➔ 7ME3610-		• IP65 (NEMA 4X) wall mount	7ME3610-	
• IP65 (NEMA 7) compact explosionproof	➔ 7ME3611-		• IP65 (NEMA 7) compact explosionproof	7ME3611-	
• IP66 (NEMA 7) wall mount explosionproof	➔ 7ME3613-		• IP66 (NEMA 7) wall mount explosionproof	7ME3613-	
	0 -			0 -	
➔ Click on the Article No. for the online configuration in the PIA Life Cycle Portal.					
Number of channels/ultrasonic paths			Sensor for channel 1		
Single path	1		(includes pipe mounting kit and spacer bar for indicated max. outer diameter listed) See "Sensor selection chart" for specifications.		
Dual path	2		no sensor	A	
Special: Four path (NEMA 4X and NEMA 7 wall mount only)	9	H 1 A	For the following B1H to D4H sensors, temperature range is -40 °C ... 65 °C (-41 °F ... 150 °F), nominal 21 °C (70 °F):		
Flowmeter functions and I/O configurations (includes graphic or digital display)			B1H (high precision) Trackmount and straps provided up to 125 mm (5")	K	
<u>IP65 (NEMA 4X) wall mount and IP66 (NEMA 7) wall mount explosionproof units</u>			B2H (high precision) Trackmount and straps provided up to 125 mm (5")	L	
• Standard (all but NEMA 7 compact explosionproof)	A		B3H (high precision) Trackmount and straps provided up to 125 mm (5")	T	
- Graphic display			C1H (high precision) ²⁾ Mounting frame and straps provided up to 600 mm (24") ¹⁾	M	
- 4 x 4 ... 20 mA analog input			C2H (high precision) ²⁾ Mounting frame and straps provided up to 600 mm (24") ¹⁾	N	
- 2 x 0 ... 10 V			D1H (high precision) ²⁾ Mounting frame and straps provided up to 1200 mm (48") ¹⁾	P	
- 2 x 4 ... 20 mA analog output			D2H (high precision) ²⁾ Mounting frame and straps provided up to 1200 mm (48") ¹⁾	Q	
- 2 x pulse output			D3H (high precision) ²⁾ Mounting frame and straps provided up to 1200 mm (48") ¹⁾	U	
- 4 x Form C relays			D4H (high precision) ²⁾ Mounting frame and straps provided up to 1200 mm (48") ¹⁾	R	
- 2 x RTD input			For the following B1H to D4H sensors, temperature range is -1 °C up to 104 °C (30 °F up to 220 °F), nominal 65 °C (150 °F):		
• Extended I/O option	B		B1H (high temperature range HP)	Z	P 1 K
- additional 2 x 4 ... 20 mA			B2H (high temperature range HP)	Z	P 1 L
- Form C relays			B3H (high temperature range HP)	Z	P 1 T
- 4 x digital pulse outputs (2 x open collector and 2 x 0 ... 5 V TTL)			C1H (high temperature range HP) ²⁾	Z	P 1 M
<u>IP65 (NEMA 7) compact explosionproof units</u>			C2H (high temperature range HP) ²⁾	Z	P 1 N
• Standard	D		D1H (high temperature range HP) ¹⁾²⁾	Z	P 1 P
- Digital display			D2H (high temperature range HP) ¹⁾²⁾	Z	P 1 Q
- 2 x 4 ... 20 mA (loop)			D3H (high temperature range HP) ¹⁾²⁾	Z	P 1 U
- 2 x 4 ... 20 mA analog input			D4H (high temperature range HP) ¹⁾²⁾	Z	P 1 R
- 2 x status (open collector)					
- 1 x RTD input					
• Digital pulse option	E				
1 x digital pulse open collector output					
Meter power options					
90 ... 240 V AC	A				
9 ... 36 V DC (except NEMA 7 compact explosionproof)	B				
9 ... 36 V DC negative GND (Compact only)	J				
9 ... 36 V DC positive GND (Compact only)	K				
Communication options					
VT100 RS 232	0				
HART, BACnet MSTP/BACnet IP, Modbus RTU & TCP/IP, Ethernet IP, Johnson N2, VT100 RS 232	2				
RTD temperature sensor (includes mounting hardware for pipes above 1.5" outer diameter)					
No RTDs	0				
1 x standard clamp-on RTD	1				
2 x standard clamp-on RTD	2				
1 x submersible clamp-on RTD	3				
2 x submersible clamp-on RTD	4				

Flow Measurement

SITRANS F US Clamp-on

SITRANS FUG1010 (Gas)

3

Selection and Ordering data	Article No.	Ord. code
SITRANS FUG1010 (Gas)	7ME3610-	
• IP65 (NEMA 4X) wall mount	7ME3611-	
• IP65 (NEMA 7) compact explosionproof	7ME3613-	
• IP66 (NEMA 7) wall mount explosionproof	0 -	
Sensor for channel 2 (includes pipe mounting kit and spacer bar for indicated max. outer diameter listed) See "Sensor selection chart" for specifications.		
no sensor	A	
For the following B1H to D4H sensors, temperature range is -40 °C ... 65 °C (-41 °F ... 150 °F), nominal 21 °C (70 °F):		
B1H (high precision) Trackmount and straps provided up to 125 mm (5")	K	
B2H (high precision) Trackmount and straps provided up to 125 mm (5")	L	
B3H (high precision) Trackmount and straps provided up to 125 mm (5")	T	
C1H (high precision) ²⁾ Mounting frame and straps provided up to 600 mm (24") ¹⁾	M	
C2H (high precision) ²⁾ Mounting frame and straps provided up to 600 mm (24") ¹⁾	N	
D1H (high precision) ²⁾ Mounting frame and straps provided up to 1200 mm (48") ¹⁾	P	
D2H (high precision) ²⁾ Mounting frame and straps provided up to 1200 mm (48") ¹⁾	Q	
D3H (high precision) ²⁾ Mounting frame and straps provided up to 1200 mm (48") ¹⁾	U	
D4H (high precision) ²⁾ Mounting frame and straps provided up to 1200 mm (48") ¹⁾	R	
Other versions (different size, mount, type or pipe larger than DN 1200 (48") or corrosion resistant), add Order code and plain text.	Z	Q 1 Y
For the following B1H to D4H sensors, temperature range is -1 °C up to 104 °C (30 °F up to 220 °F), nominal 65 °C (150 °F):		
B1H (high temperature range HP)	Z	Q 1 K
B2H (high temperature range HP)	Z	Q 1 L
B3H (high temperature range HP)	Z	Q 1 T
C1H (high temperature range HP) ²⁾	Z	Q 1 M
C2H (high temperature range HP) ²⁾	Z	Q 1 N
D1H (high temperature range HP) ²⁾	Z	Q 1 P
D2H (high temperature range HP) ²⁾	Z	Q 1 Q
D3H (high temperature range HP) ²⁾	Z	Q 1 U
D4H (high temperature range HP) ²⁾	Z	Q 1 R
Approvals		
FM/CSA/CE/C-TICK (default)	1	
ATEX, CE, C-TICK	2	

¹⁾ Supplied spacer bar supports pipes up to 750 mm (30 inch). For pipes larger than 750 mm (30 inch) purchase also, spare part 7ME3960-0MS40 (1012BN-4).
²⁾ Made with stainless steel construction.

Selection and Ordering data	Order code
Further designs	
Please add "-Z" to Article No. and specify Order code(s).	
Cable assembly for sensors (add for # of paths) See "Sensor cable selection chart"	K..
Cable assembly for RTDs (add for # of RTDs) See "RTD cable selection chart"	R..
Cable termination kit (for one cable pair)	
• Termination for standard, plenum and armored sensor cable	T01
• Termination for submersible sensor cable	T11
• RTD cable termination kit for standard RTD	T21
• RTD cable termination kit for submersible RTD	T31
• Insert RTD cable termination kit	T41
• Cable gland kit	T51
Languages (Meter and Documentation) for compact NEMA 7	
• German	B10
• French	B12
• Spanish	B13
• Italian	B14
Tag name plate	
• Stainless steel tags with 3.2 mm (0.13 inch) characters (68 characters max.)	Y19

MLFB example

Application example

A clamp-on meter is required for a 300 mm (12") carbon steel gas line with a wall thickness of 12.7 mm (0.5"). Meter electronics are to be located in a Class I Div 2 area only 18 m (60 ft) from the pipeline. 12 V DC power is available at the site.

Dual path operation is desired for improved accuracy and redundant measurement. Pulse output will be primary flow data source.

MLFB Article No.: **7ME3610-2BB00-0QQ1-Z**
K03 + K03

Selection and Ordering data	Article No.	Ord. code
SITRANS FUG1010 meter family	7 ME 3 6 1 -	0 -
IP65 (NEMA 4X) wall mount	0	
Dual path	2	
Option with digital pulse	B	
9 ... 36 V DC power option	B	
RS 232 Standard	0	
No RTD required	0	
Sensor code for path 1	Q	
Sensor code for path 2	Q	
FM approval required	1	
30 m (100 ft) sensor cab. for path 1		K 0 3
30 m (100 ft) sensor cab. for path 2		K 0 3

Selection and Ordering data	Article No.
Operating Instructions for SITRANS FUG1010	
English NEMA 4X wall mount & NEMA 7 wall mount explosionproof	A5E02951519
German NEMA 4X wall mount & NEMA 7 wall mount explosionproof	A5E02951531
English NEMA 7 compact explosionproof	CQO:1010GCXFM-3

This device is shipped with a Quick Start Guide and a CD containing further SITRANS F literature.

All literature is also available for free at:
<http://www.siemens.com/flowdocumentation>

High precision sensor selection chart IP68

Based on pipe wall thickness (steel pipes only)					
Sensor Pipe wall	Order Code	Pipe wall (mm)		Pipe wall (inch)	
		min.	max.	min.	max.
B1H	K	2.0	3.0	0.08	0.12
B2H	L	3.0	4.1	0.12	0.16
B3H	T	2.7	3.3	0.106	0.128
C1H ¹⁾	M	4.1	5.8	0.16	0.23
C2H ¹⁾	N	5.8	8.1	0.23	0.32
D1H ¹⁾	P	8.1	11.2	0.32	0.44
D2H ¹⁾	Q	11.2	15.7	0.44	0.62
D3H ¹⁾	U	7.4	9.0	0.293	0.354
D4H ¹⁾	R	15.7	31.8	0.62	1.25

¹⁾ Made with stainless steel construction.

Sensor Cable (pair) Selection Chart

Sensor cable codes for length and type options				
Cable length m (ft)	Standard (PVC jacket)	Submersible (polyethylene jacket)	Plenum Rated (teflon jacket)	Armored
	-40...+80 °C (-40...+176 °F)	-40...+80 °C (-40...+176 °F)	-40...+200 °C (-40...+392 °F)	-40...+80 °C (-40...+176 °F)
Order code				
6 (20)	K01¹⁾	K11	K21	K31
15 (50)	K02	K12¹⁾	K22	K32¹⁾
30 (100)	K03¹⁾	K13¹⁾	K23	K33
46 (150)	K04¹⁾	K14	K24	K34
61 (200)	K05	K15	K25	K35
91 (300)	K06¹⁾	K16	K26	K36

¹⁾ Standard MLFB for quick deliver

RTD Cable (single) Selection Chart

RTD cable codes for length and type		
Cable length m (ft)	Standard (teflon wrapped)	Submersible (extruded jacket)
	-40 ... +200 °C (-40 ... +392 °F)	-40 ... +200 °C (-40 ... +392 °F)
Order code		
6 (20)	R01¹⁾	R11
15 (50)	R02¹⁾	R12
30 (100)	R03¹⁾	R13
46 (150)	R04	R14
61 (200)	R05	R15
91 (300)	R06	R16

¹⁾ Standard MLFB for quick deliver

Flow Measurement

SITRANS F US Clamp-on

SITRANS FUG1010 Gas check metering kit

Overview



The clamp-on SITRANS FUG1010 Gas check metering kit is an all-inclusive solution developed especially for verifying the accuracy and performance of any brand or type of flowmeter. The kit is ideal for natural and process gas applications, including check metering, allocation, production, storage and gas fired power station applications. The flowmeter is available with FM/CSA or ATEX approval.

Benefits

- Performance check or verification of any type or brand of flow meter
- WideBeam technology provides improved accuracy over a wide range of flow velocity and operating pressure
- Tolerant of most wet gas conditions
- Immune to most pressure reducing valve noise
- Fast, easy and cost-efficient on-site measurement of any convoluted pipe from 50 ... 1200 mm (2 ... 48") up to 15.7 mm (0.62") pipe wall thickness
- Delivered as an all inclusive kit in a sturdy rolling case that holds all the equipment needed to conduct performance and verification tests (cables, multiple sensors, transmitter, etc.)

Application

The SITRANS FUG1010 Gas check metering kit is ideal for most natural and process gas industry applications, including:

- Check metering
- Allocation
- Flow survey verification
- Lost and unaccounted for (LAUF) gas analysis
- Production
- Storage

Design

- IP65 (NEMA 4X) wall mount enclosure constructed of fiberglass reinforced polyester with stainless steel hardware and polyester keypad
- Dual channel

Function

- Integral 33 button keypad and large (128 x 240 pixel) graphic display visible up to 12 m (40 ft) away
- Current, voltage, frequency and RS 232 outputs (see Technical specification section for details)
- Analog inputs for pressure and temperature
- Internal AGA-8 table for fixed gas composition is available for standard volume computation
- Upward compatibility and compliance with AGA-10 speed of sound measurement practice
- Bi-directional flow operation
- English, Spanish, German, Italian and French language options

Technical specifications

Pipe sizes	50 ... 1200 mm (2 ... 48") up to 15.7 mm (0.62") pipe wall thickness
Accuracy	±0.5 %...1.0 % of flow rate
Flow range	30 m/s (100 ft/s) bidirectional
Media temperature	-40 ...+60 °C (-40 ... +140 °F)
Enclosure ratings	IP65 (NEMA 4X)

See page 3/368 for complete technical specifications

Certificates and approvals

FM and CSA

- Transmitter
N-I Class I, Div 2
S Class II, Div 2
- Sensor
I.S. Class I, II, Div 1

ATEX

- Transmitter:
Ex II (1) G [Ex ia] IIC
Ex II 3 (1) G Ex nC [ia] IIC T5

CE

- Sensors:
Ex II 1 G Ex ia IIC T5
EMC Directive 2004/108/EC
ATEX Directive 94/9/EC

Selection and Ordering data

Article No.

SITRANS FUG1010 Gas Check Metering Kit

- FM/CSA approved
- ATEX approved

CQO:FUG-GASKIT
CQO:FUG-GASAKIT

Content of delivery

1	Dual channel dedicated transmitter (FM/CSA or ATEX approved)
1 pair	Transportable sensors C1 ¹⁾ Pipe: od 3.500 inch, wt 0.216 inch, carbon steel
1 pair	Transportable sensors C2 ¹⁾ Pipe: od 6.625 inch, wt 0.280 inch, carbon steel
1 pair	Transportable sensors D1 ¹⁾ Pipe: od 10.750 inch, wt 0.365 inch, carbon steel
1 pair	Transportable sensors D2 ¹⁾ Pipe: od 16.000 inch, wt 0.500 , carbon steel
2 pairs	Sensor cables 6m (20 ft)
2 pairs	Mounting frames
2	Spacer bar (dedicated)
1	Mounting strap
4	Couplant CC128
1 kit	Couplant/Damping Film
1	Flow case
1	Flowmeter manual
1	Laminated card set

¹⁾ Made with stainless steel construction.